HellermannTyton

Solar Label, Printable, Spanish, AC MODULE, 4.0" x 2.0",

Article Number: 59

VIDITAJE INOMINAL DE OPERACIÓN DE CA FRECUENCIA NOMINAL DE OPERACIÓN DE CA POTENCIA MÁDINA DE CA CORRENTE MÁDINA DE CA SOBRECORBUTE NOMINAL INÁLINA DEL DISPOSITIVO PARA PROTECCIÓN DEL MODULO DE CA

: 596-00816

PET, Red, 50/roll

Base Data Local Order Number 596-00816 AC2011S Type Color Red (RD) Features and benefits • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. · High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. Quantity Per roll **Product Description** HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. **Technical Description** Printable Solar Label, Spanish Version, AC MODULE LABEL, 4.0" X 2.0", Red Local Order Number 2 English Version: 596-00252 Solar Label, Printable, Spanish, AC MODULE, 4.0" x 2.0", PET, Red, 50/roll Short Description Product Dimensions Length L (Imperial) 4.0" Length L (Metric) 101.6mm Width W (Imperial) 4.0" Width W (Metric) 101.6mm Height H (Imperial) 2.0" Height H (Metric) 50.8mm Material and Specifications Material Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

596-00816

HellermannTyton

Material and Specifications	Material Shortcut	840/926
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1