

Article Number: 596-00846

AWARNING
INVERTER OUTPUT
CONNECTION. DO
NOT RELOCATE
THIS OVERCURRENT
DEVICE.

Description: Solar Label, WARNING INVERTER

OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL,

Orange, 50/roll

Base Data		
	Local Order Number	596-00846
	Туре	IOCOD14
	Color	Orange (OG)
	Features and benefits	 Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. Supplied with an aggressive adhesive to ensure long life. Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label," WARNING - INVERTER OUTPUT CONNECTION", 2.0" X 1.25", Orange
	Short Description	Solar Label, WARNING INVERTER OUTPUTOVERCURRENT DEVICE, 2.0" x 1.25", VL, Orange, 50/roll
Product Dimensions		
	Length L (Imperial)	1.25"
	Length L (Metric)	31.75mm
	Width W (Imperial)	2.0"
	Width W (Metric)	50.8mm
	Height H (Imperial)	1.25"
	Height H (Metric)	31.75mm
Material and Specifications		
	Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate

generated on: 4/29/2017

596-00846



Material and Specifications	Material Shortcut	443/552
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055

generated on: 4/29/2017