

151-40100



Article Number: 151-40100

Description: Push-Button Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

Base Data	
Local Order Number	TM1SF0C2
Type	TM1SF
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Push Mounts, when used with standard cable ties, provide a permanent bundling solution. • The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.
Quantity Per	bag
Product Description	HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.
Short Description	Push-Button Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg
Product Dimensions	
Length L (Imperial)	0.62"
Length L (Metric)	15.8mm
Fixation Method	with Arrowhead / Push Mount (Mounts)
Width W (Imperial)	0.4"
Width W (Metric)	10.2mm
Cable Tie Width Max. (Imperial)	0.2"
Cable Tie Width Max. (Metric)	5.0mm
Height H (Imperial)	0.18"
Height H (Metric)	4.6mm
Height H2 (Imperial)	0.18"
Height H2 (Metric)	4.6mm
Panel Thickness Max. (Imperial)	0.13"
Panel Thickness Max. (Metric)	3.3mm
Panel Thickness Min. (Imperial)	0.13"

151-40100



Product Dimensions	Panel Thickness Min. (Metric)	3.40mm
	Mounting Hole Diameter D (Imperial)	0.25"
	Mounting Hole Diameter D (Metric)	6.35 mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987