

Heavy Duty Fuse Clip, 6.3x32 mm, 600 VAC/VDC, 32 A



Solder THT version tin-plated



Solder THT version silver-plated

600 VAC/DC · 32 A (UL)



**Description**

- Solder mounting

**Unique Selling Proposition**

- Unique 600 VAC/VDC and 32 A  
- Minimal power loss due to strong clamping force

**Standards**

- UL 4248-1  
- CSA 22.2 no. 4248.1

**Approvals**

- UL File Number: E39328

**Applications**

- Photovoltaic

**References**

Fuseholder to [SUT 6.3x32](#)

**Weblinks**

[pdf datasheet](#), [html-datasheet](#), [General Product Information](#), [Packaging details](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Distributor-Stock-Check](#), [Detailed request for product](#)



**Technical Data**

Fuse-Link	6.3 x 32mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	600VAC/DC
Rated current	32A (UL)
Admissible Ambient Air Temp.	-55 °C to 125 °C
Material: Terminals	Copper alloy, silver-plated / tin-plated 1)
Storage Conditions	0 °C to 60 °C, max. 70% r.h.

Soldering Methods	Wave <a href="#">Soldering Profile</a>
Solderability	245 °C / 3 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A
Contact Resistance	≤ 10 mΩ at 20 mV

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

**Dimension**



Drilling diagram

**All Variants**

Clip	Material: Terminals	Order Number
●	Tin-plated	8040.0001
●	Silver-plated	8040.0003

Most Popular.

Availability for all products can be searched real-time:<http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

---

<b>Packaging Unit</b>	Bulk (1000 pcs.)
-----------------------	------------------

---