

169-60504



Article Number: 169-60504

Description: Convoluted Tubing, Slit, 1.25" Dia, PE, Black, 1800 ft/carton

Base Data	
Local Order Number	CTP1140
Type	CTP1140
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.
Quantity Per	carton
Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Technical Description	Convoluted Tubing, Slit, 1-1/4" Dia., PE, Black
Short Description	Convoluted Tubing, Slit, 1.25" Dia, PE, Black, 1800 ft/carton
Product Dimensions	
Length L (Imperial)	1800.0ft
Length L (Metric)	548.6m
Inner Diameter D (Imperial)	1.257"
Inner Diameter D (metric)	31.93mm
Diameter D (imperial)	1.50"
Diameter D (metric)	38.10mm
Diameter D2 (imperial)	1.257"
Diameter D2 (metric)	31.93mm
Outside Diameter D (imperial)	1.50"

169-60504



Product Dimensions	Outside Diameter D (metric)	38.10mm
	Nominal Diameter (Imperial)	1-1/4"
	Nominal Diameter (Metric)	31.75mm
	Wall Thickness WT (Imperial)	.006"
	Wall Thickness WT (Metric)	0.152mm
Material and Specifications		
	Material	Polyethylene (PE)
	Material Shortcut	PE
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +199°F (-40°C to +93°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1800ft
	Package Quantity (Metric)	548.6m
	Customs Number(Schedule B)	3926909987