



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: P608-020

Computer Cable, 20-ft. IEEE 1284 AC Parallel Cable DB25M to MicroCen36M

Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- IEEE 1284 cables' gold-plated connectors provide superior conductivity and support high-speed bi-directional printing



Description

Tripp Lite's 20-ft. IEEE 1284 A-C parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Micro Centronics 36 female parallel port. The cable has DB25 male/MicroCent36 male connectors and supports high-speed IEEE 1284 bi-directional communication. It is manufactured from superior molded cable with integral strain relief and double shielding for maximum EMI/RFI protection. It contains low-capacitance, impedance matched, twisted-pair conductors that protect against cross-talk and other transmission problems. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Micro Centronics 36 Female parallel port with high-speed IEEE 1284 Bi-Directional communication.

Package Includes



- 20-ft. IEEE 1284 AC Parallel Cable DB25M to MicroCen36M

Features

- Supports high-speed IEEE 1284 bi-directional communication (modes: standard compatible nibble byte ECP and EPP)
- Length: 20-ft. Connectors: DB25 male/MicroCent36 male
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

INPUT	
Cable Length (ft.)	20
UPC Codes	

Unit Carton UPC#	037332013637
CONNECTIONS	
Connector A	 DB25 (MALE)
Connector B	 MINI CENTRONICS 36 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2300.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.