

Cable gland - G-INS-M25-M68N-PNES-GY - 1411126

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide 6, External cable diameter 11 mm ... 17 mm, Shielding: No, Connecting thread: M25



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	16.0 g
Custom tariff number	39269097
Country of origin	Turkey

Technical data

Dimensions

Length	42 mm
Wrench size, union nut	29 mm
Wrench size, support	29 mm
Hexagon angular dimension GRP	33.5 mm
Length of the connecting thread	8 mm
Feed-through hole diameter	25.1 mm ... 25.2 mm
External cable diameter	11 mm ... 17 mm

Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-20 °C ... 100 °C (static)

General

No. of conductors	1
Cable gland material	Polyamide 6
Seal material	Neoprene

Cable gland - G-INS-M25-M68N-PNES-GY - 1411126

Technical data

General

Cable seal material	Neoprene
Shielded	No
Thread type on connection side	M25
Torque	3.5 Nm (Union nut)
Flammability rating according to UL 94	V2
Color	silver-grey RAL 7001

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

CSA / VDE Zeichengenehmigung / UL Listed / cUL Listed / cULus Listed


Ex Approvals

Approvals submitted

Approval details

Cable gland - G-INS-M25-M68N-PNES-GY - 1411126

Approvals



Drawings

Dimensional drawing

