



Bayonet Channel x 3

Protective Cap
(Bayonet Locking Type)

Tether

(b)

(c)

Notes:

1. Material:

- Protective Cap: PBT(Black); UL94 V-0
- Tether: PE (Black)

- Operating Temperature: -40°C to +85°C

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				Tolerance Unless otherwise specified 0. ±0.50 0.0 ±0.38 0.00 ±0.25 Angles ±3°		dim. in mm		scale: 2:1 (1,5:1) material: see notes			
				date	name		title:				
				drawn	05.11.13	Strakerjahn		(d) Protective Cover for IP67 Duplex Power 2+3pos Male Receptacle Assembly			
				appd.	05.11.13	Koch					
				1 x d	Ä6182	06.06.2016	K.H.	norm	dwg no:		DIN-A3
			1 x c	Ä5616	21.04.15	K.H.	d-old	17K1A430		sh: 1	
			a	Original			part no:		17-400260		

RoHS compliant

