



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP48V60RT-3U

External Battery Pack and Cable. 3U, Expandable, Blue 2-Point Connector

Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 48VDC external battery connector
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower and stack adaptable



Description

BP48V60RT3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP48V60RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation.
COMPATIBLE UPS SYSTEMS - SMART2200RMXL2U, SMART2600RM2U, SMART3000RM2U, SMART5000RT3U, SMX5000XLRT3U, SMX3000XLRT2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP48V60RT3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Additional output connector allows multiple BP48V60RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation

Specifications

BATTERY	
Expandable battery runtime	Blue 175 amp female connector for additional battery packs
DC system voltage (VDC)	48

Connects to UPS via	20 inch attached cable with blue 175 amp male DC connector
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	200.6
Shipping weight (kg)	91.1
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.3 x 44.4 x 63.5
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.6 x 58.4 x 80
Unit weight (lbs)	163.1
Unit weight (kg)	74
Material of construction	Steel
Form factors supported	3U rack/tower
ENVIRONMENTAL	
Operating Temperature	32-104 degrees F / 0-40 degrees C
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Optional Products

Related Model	Description	Qty.
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
WEXT3-BP48V60	3-Year Extended Warranty - For BP48V60RT3U and BP48V60RT3UTAA Battery Packs	1
WEXT5-BP48V60	5-Year Extended Warranty - For BP48V60RT3U and PB48V60RT3UTAA Battery Packs	1
2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2502.

