



FEATURES

- Micro package
- Photoconductive
- Low cost
- High speed

DESCRIPTION

The **PDB-C145** is a blue enhanced PIN silicon photodiode in a photoconductive mode packaged in a water clear lensed micro plastic package.

APPLICATIONS

- Smoke detectors
- Data links
- Scanners

ABSOLUTE MAXIMUM RATING (TA)= 25°C UNLESS OTHERWISE NOTED

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{BR}	Reverse Voltage		50	V
T _{STG}	Storage Temperature	-50	+125	°C
T _O	Operating Temperature	-40	+105	°C
T _S	Soldering Temperature*		+260	°C

* 1/16 inch from case for 3 seconds max.

ELECTRO-OPTICAL CHARACTERISTICS RATING (TA)= 25°C UNLESS OTHERWISE NOTED

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
V _f	Forward Voltage	I _f = 10 mA, H = 0	0.5		1.3	V
I _D	Dark Current	V _R = 2.5 V, H = 0			10	nA
I _{sc}	Short Circuit Current	V _R = 5V, 2850°K, 1000lux		8		uA
C _J	Junction Capacitance	V _R = 3 V, f = 1 MHz, H=0		3		pF
λ range	Spectral Application Range	Spot Scan	400		1050	nm
V _{BR}	Breakdown Voltage	I = 100 μA, H = 0	35			V
t _r	Response Time	RL = 1KΩ, V _R = 3 V		10		nS

**Response time of 10% to 90% is specified at 660nm wavelength light.

Information in this technical datasheet is believed to be correct and reliable. However, no responsibility is assumed for possible inaccuracies or omission. Specifications are subject to change without notice.