

◆STANDARD SIZE

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL (mm)	Ripple Current (A.r.m.s 105°C,120Hz)
350	1800	51×98	5.5
	2200	51×118	6.2
	2700	51×138	7.0
	3300	64×109	8.4
	3900	64×119	9.2
	4700	64×139	10.2
	5600	77×121	12.6
	6800	64×189	12.6
	6800	77×141	14.1
	8200	90×121	18.3
	10000	77×191	17.5
	10000	90×151	20.8
	12000	90×191	23.5
	15000	90×221	26.5
	18000	90×241	29.0
400	1200	51×98	4.7
	1500	51×118	5.3
	1800	51×118	5.8
	2200	51×138	6.5
	2700	64×119	8.0
	3300	64×139	8.9
	3900	64×149	9.7
	4700	77×121	12.0
	5600	64×189	11.8
	5600	77×141	13.2
	6800	90×141	18.0
	8200	77×191	16.3
	8200	90×151	19.5
	10000	90×191	22.1
	12000	90×221	24.1
15000	90×241	27.4	

Rated Voltage (Vdc)	Capacitance (μF)	Size φDXL (mm)	Ripple Current (A.r.m.s 105°C,120Hz)
450	1000	51×98	4.3
	1200	51×118	4.8
	1500	51×118	5.3
	1800	51×138	5.9
	2200	64×119	7.2
	2700	64×139	8.0
	3300	64×149	8.9
	3900	64×189	9.9
	3900	77×141	11.0
	4700	90×121	14.6
	5600	90×141	16.2
	6800	77×191	14.9
	6800	90×151	17.8
	8200	90×191	20.0
	10000	90×221	22.4
12000	90×241	24.6	

◆Tightening torque of bolt and Permissible current of terminal

Clamp Bolt	Recommended Tightening torque
M3	0.6 [N·m]
M4	1.3 [N·m]

Terminal	Recommended Tightening torque (Permissible Range)	Permissible Current of Terminal
M5	2.2(1.5~3.2) [N·m]	60[A r.m.s.]