



- NOTES:**
- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
 - INSULATORS: PBT GF UL 94 V-0, BLACK
 - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.)
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - METAL BRACKETS: ZINC DIE CAST; 300µm COPPER/40-120µm NICKEL/120-200µm TIN
 - THREADED LOCKS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 - FIXING PLATE: PBT GF UL 94 V-0, BLACK
 - MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
 - CONNECTOR IS PART MARKED: 163□15679X CONEC ABC

Directive 2002/95/EC RoHS compliant

finish:				tolerance		dim. in mm	scale: 2:1	
				material: SEE NOTES				
DO NOT ALTER CAD DRAWING BY HAND				date	name		title: D-SUB DUAL PORT 19.05mm 9pos. MALE / 9pos. MALE threaded lock, metal bracket and fixing-plate	
				drawn	09.09.09 Sonenberg			
				appd.	09.09.09 Koch			
				norm				
1 x b A4361 03.07.2012 K.H.				d-old			dwg no:	
a Original				CONEC®		16K1A2542		DIN-A3
rev. description date name						part no: 163□15679X (see note 3)		sh: 1