

118-05900



Article Number: 118-05900

Description: Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

Base Data	Local Order Number	118-05900
	Type	T50LOS
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Outside serrations minimize damage to cables, while still providing high tensile strength and low insertion force. • Contour style head design provides additional space in constrained areas. • Heat stabilized material provides excellent resistance to high heat exposures.
	Quantity Per	bag
	Product Description	HellermannTyton outside serrated cable ties are designed with a smooth inside surface to help minimize indentation or damage to wire and cable insulation, while offering high tensile strength and low insertion force. The contour style head takes up less space than traditional style cable ties making it ideal for space constrained areas. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225.0N
	Length L (Imperial)	15.0"
	Length L (Metric)	384.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Outside Serrated
	Width W (Imperial)	0.18"
	Width W (Metric)	4.6mm
	Height H (Imperial)	0.051"
	Height H (Metric)	1.3mm

118-05900



Product Dimensions	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.6mm
	Bundle Diameter Max. (Imperial)	4.3"
	Bundle Diameter Max. (Metric)	110.0mm
	Thickness T (Imperial)	0.05"
	Cable Tie Head Length (Imperial)	0.26"
	Cable Tie Head Width (Imperial)	0.31"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
ROHS Compliant	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	4kg